



PHR-4017I

8路电流输入模块

- 分辨率:16位
- 通道数:8路差分电流
- 输入信号类型:4-20mA、0-20mA、±20mA
- 数据更新速率:250ms
- 采样频率:10Hz
- 输入阻抗:120 Ohms
- 精度:0.1%F.S(典型值为0.05%F.S)
- 温度漂移:0.005%F.S/*C
- 供电电源:18~30VDC
- 最大功耗:1.2W/24VDC
- 隔离电压:3000VDC
- 工作温度:-20*C~70C
- 存储温度:-40*C~85*C
- 湿度:5%~90%, 无凝露

PHR-4017I

8-channel current input module

- Resolution: 16 bit
- Channel number: 8-channel differential current
- Input signal type: 4-20mA, 0-20mA ±20mA
- Data update rate: 250ms
- Sampling frequency: 10Hz
- Input impedance: 120Ohms
- Accuracy: 0.1% F.S (typical value is 0.05% F.S)
- Temperature drift: 0.005% F.S / °C
- Power supply: 18 ~ 30VDC
- Maximum power consumption: 1.2w/24vdc
- Isolation voltage: 3000vdc
- Working temperature: - 20 °C ~ 70c
- Storage temperature: - 40°C ~ 85°C
- Humidity: 5% ~ 90%, no condensation