



PHR-4022

2路隔离模拟量输出模块

- 分辨率:16位
- 通道数:2路隔离输出
- 输出信号类型:420mA、0-20mA、0-5V、0-10V、 $\pm 10V$
- 过电压保护: $\pm 35V$
- 带载能力: $\leq 350\Omega$ (20mA)
- 精度:0.1%F.S(典型值为0.05%F.S)
- 温度漂移:0.005%F.S/ $^{\circ}C$
- 供电电源:18~30VDC
- 最大功耗:1.2W/24VDC
- 隔离电压:3000VDC
- 工作温度:-20 $^{\circ}C$ ~70 $^{\circ}C$
- 存储温度:-40 $^{\circ}C$ ~85 $^{\circ}C$
- 湿度:5%~90%,无凝露

PHR-4022

2 channel isolated analog output module

- Resolution: 16 bit
- Channel number: 2 channel isolated output
- Output signal type: 4-20mA, 0-20mA 0-5v, 0-10V $\pm 10V$ over
- Voltage protection: $\pm 35V$
- Load capacity: $\leq 350\Omega$ (20mA)
- Accuracy: 0.1% F.S (typical value is 0.05% F.S)
- Temperature drift: 0.005% F.S / $^{\circ}C$
- Power supply: 18 ~ 30VDC
- Maximum power consumption: 1.2w/24vdc
- Isolation voltage: 3000vdc
- Working temperature: - 20 $^{\circ}C$ ~ 70 $^{\circ}C$
- Storage temperature: - 40 $^{\circ}C$ ~ 85 $^{\circ}C$
- Humidity: 5% ~ 90%, no condensation