



## PHR-4024V

4路电压输出模块

- 分辨率:16位
- 通道数:4路输出
- 输出信号类型:0-5V、0-10V、 $\pm 10V$
- 精确度:0.1%F.S
- 温度漂移:0.005%F.S/ $^{\circ}C$
- 供电电源:18~30VDC
- 最大功耗:1W/24VDC
- 隔离电压:3000VDC
- 工作温度:-20 $^{\circ}C$ ~70 $^{\circ}C$
- 存储温度:-40 $^{\circ}C$ ~85 $^{\circ}C$
- 湿度:5%~90%,无凝露

## PHR-4024V

4-way voltage output module

- Resolution: 16 bits
- Channel number: 4-way output
- Output signal type: 0-5V, 0-10V  $\pm 10V$
- Accuracy: 0.1%F.S
- Temperature drift: 0.005%F.S/ $^{\circ}C$
- Power supply: 18 ~ 30VDC
- Maximum power consumption: 1W / 24VDC
- Isolation voltage: 3000vdc
- Working temperature: - 20  $^{\circ}C$  ~ 70  $^{\circ}C$
- Storage temperature: - 40  $^{\circ}C$  ~ 85  $^{\circ}C$
- Humidity: 5% ~ 90%, no condensation